Pache SARL - 64 Route de Gravin, 74300 Magland
04 50 89 57 17 contact@pache-adler.fr
www.pache-adler.fr

Technical data sheet

ADLER
In unseren Adern fließt Farbe.

ADLER Abbeizer "Rote Krähe" (Red Crow) 95125



Properties

Free from chlorinated hydrocarbons and aromatic hydrocarbons, pleasant odour and drop-inhibited.

Areas of application

Suitable for 1-component paints such as synthetic resin paints, acrylic paints, emulsions and synthetic resin plasters on wood, metal and brickwork. Trials are recommended for 2-components paints.

Application method

Natural hair brush, airless device

Processing

Apply uniformly and generously. Use a wet-on-wet application again with stronger paint layers. Covering the caoted surfaces with PE film improves the effect of the staining process.

Push off layers of paint that have completely peeled off or use a high-pressure cleaner (70 – 90 °C). Rinse thoroughly with water.

Soaking time

Depending on the type and tickness of the coat to be stained, emulsion paints peel off after 30 minutes to 4 hours, and coated paints after several hours.
If possible, allow it to soak overnight.

Processing and object temperature

A temperature of 20 °C is optimal. ADLER Abbeizer "Rote Krähe" (Red Crow) 95125 can also be applied at low temperatures, whereby the staining process gets delayed. Avoid direct sunlight.

Tools and Equipment

Clean them with water immediately after use. Dry spraying devices well when finished in order to prevent rusting.

Yield (per application)

Approx. 4 m²/l per coat of paint

Container sizes

750 ml and 2.5 l

Safety-relevant information

Do not dispose of paint residues contamined with the stain or washing water with household waste, but hand them over to specialist waste collection agencies.
Please take note of and follow the safety data sheet!

PACHE sarl

01-10 (supersedes 06-03)

ADLER-Werk Lackfabrik, A-6130 Schwaz
Tel.: 0043/5242/6922-301, Fax: 0043/5242/6922-399, E-mail: technical-support@adler-lacke.com

Our instructions for use are based on knowledge available currently and shall guide the purchaser / user to the best of one's knowledge, but, however, must be clarified for the areas of application and processing conditions on a case-to-case basis. The purchaser / user decides about the acceptance and use of the delivered product at his / her own risk, which is why we recommend that a sample piece be prepared to check the acceptability of the product. Our general terms and conditions of sale are otherwise applicable. All previous data sheets are rendered invalid with the issue of this one. Rights reserved for the modification of the container sizes, colour shades and degrees of gloss available.