Pache SARL - 64 Route de Gravin, 74300 Magland
04 50 89 57 17 contact@pache-adler.fr
www.pache-adler.fr

Technical data sheet

ADLER
Paint runs through our veins.

Aqua-Hardener 8450 8450

Hardener for water-based ADLER paint/varnish systems, for use in **industry and trade**

PRODUCT DESCRIPTION

Product numbers

8450000210

General

Polyisocyanate hardener for water-based paint/varnish systems.

Application area

Hardener component for water-based ADLER furniture coatings for furniture and interior finishing.

Hardener component for water-based two-component window and front door coatings.

PROCESSING

Processing instructions

- Immediately after adding Aqua-Hardener 8450 (8450) to the paint component, blend in carefully. We recommend waiting approx. 10 minutes before starting work.
- Mixed paints and stains must be processed as specified in the corresponding technical data sheet.

Cleaning the working equipment

8029

To remove dried paint residues we recommend using Aqua-Cleaner (8029) (diluted 1:1 with water).

Please follow our **ARL 150 - Working guidelines for water-based furniture coatings.**

Please refer to the corresponding technical data sheets of the products.

ORDERING INFORMATION

Size of trading unit

200 g, 280 g, 770 g, 1.1 kg, 9 kg, 25 kg

PACHE sarl

ADLER-Werk Lackfabrik, A-6130 Schwaz
Fon: +43/5242/6922-190, Fax: +43/5242/6922-309, Mail: technical-support@adler-lacke.com

Our instructions are based on the current state of knowledge and are intended to advise the buyer/user to the best of our knowledge, but must be individually adapted to the areas of application and processing conditions. The buyer/user is responsible for deciding on the suitability and use of the supplied product, which is why we recommend that a sample be produced to check the suitability of the product. In all other respects, our General Terms and Conditions of Sale apply. All previous data sheets lose their validity with this edition. We reserve the right to make changes to container sizes, color shades and available gloss levels.

Pache SARL - 64 Route de Gravin, 74300 Magland
04 50 89 57 17 contact@pache-adler.fr
www.pache-adler.fr

FURTHER DETAILS

Durability / storage



Min. 6 unit.month in the original sealed containers.

Make sure the product is protected against moisture, direct sunlight, frost and high temperatures (above 30 °C).

Immediately seal the container to prevent humidity from penetrating.

Close opened containers well and use up the content as soon as possible.

Safety information

The product is only suitable for the industrial and professional use.

Further information on the subject of safety during transport, storage and handling as well as disposal can be found in the relevant safety data sheet. The current version can be accessed on the Internet at **www.adler-lacke.com.**

PACHE sarl