Pache SARL - 64 Route de Gravin, 74300 Magland
04 50 89 57 17 contact@pache-adler.fr
www.pache-adler.fr

Technical data sheet

ADLER Formel-Fresh 96360

Product description

Wall paint activator for air purification.
ADLER Formel-Fresh is added to paint for living spaces as an additive and has a catalytic effect on odorants and toxic substances.

Special properties

The product reduces poisons in living spaces (e.g. formaldehyde) an odours of every day life (e.g. kitschen smells, pets, cigarette smoke).

Free from emissions and solvents, unplasticised, odourless.

Areas of application

To reduce odours and poisons in living spaces in all interior rooms, both for residential and commercial use.

Quantity to be added

The **quantity to be added** is **250 ml to 9 l of paint**.

Tested as an additive in the paints for living spaces ADLER Formel 2000 40205, ADLER Formel 1 40202, ADLER Tiromin 40301 und ADLER Isocryl 40281.

Note: In systems rich in binding agents such as lacquers and latex paints, the effect of Formel-Fresh is reduced.

Incorporation

Shake container well before use!

Shake paint container for 2 minutes after adding ADLER Formel-Fresh!

Mode and duration of effect

The decomposition reaction is relatively slow and goes on for days. The effect of the activator does not dissipate, it is permanent and does not require light.

The larger the coated surface in relation to the room volume, the better the cleansing effect.

In order to achieve good effectiveness, you require at least 0.4 m^2 coated surface for 1 m^3 room volume.

Processing temperature

Not below + 5 °C

Storage

Cool but frost-free

Storage stability

3 years

Packaging

250 ml (sufficient for 9 l of paint for interior walls)

Safety-relevant information

Please take note of and follow the safety data sheet!

09-10 (supersedes 07-07) ZKL 4009

ADLER-Werk Lackfabrik, A-6130 Schwaz
Fon: 0043/5242/6922-190, Fax: 0043/5242/6922-309, Mail: info@adler-lacke.com

Our instructions are based on the current knowledge and are intended to advise the buyer/user to the best of our knowledge. They must be, however, individually adapted to the application areas and conditions. The buyer/user takes responsibility for the suitability and use of the delivered product. It is therefore recommended to produce a sample specimen for testing the suitability of the product. Otherwise our General Terms of Sale apply. All previous specifications become invalid with this edition. Packaging sizes, colors and available gloss values are subject to change.

PACHE sarl