**Pache SARL** - 64 Route de Gravin, 74300 Magland
04 50 89 57 17 contact@pache-adler.fr
www.pache-adler.fr

# Technical data sheet

ADLER
Paint runs through our veins.

## Grilith Klarlack-Spray 2417

**Solvent-based clear coating spray** for interior use for **professional and industrial use**

## PRODUCT DESCRIPTION

### General

Rapid-drying repair spray clear coating based on nitrocellulose for coated furniture surfaces. The product is characterised by very rapid drying and good flow. Spray application without lap marks.

### Special properties and standards

ADLER QUALITY CHECK

- **ÖNORM A 1605-12 (furniture surfaces)**
  Resistance to chemical reactions: 1-C

### Application area

Small-scale touch-up work in furniture and interior finishing.

For touching-up assembly scratches

To touch-up damage

## PROCESSING

### Processing instructions

- The temperature of the product and object, and the room temperature must be at least + 15 °C.
- Shake can vigorously for 2 minutes before use. Mixing ball must be audible. Shake occasionally during use.
- Hold the can upright when spraying and apply evenly at room temperature from a distance of approx. 20 - 30 cm, avoiding excessive application.
- To assess colour and grain enhancement uniformity as well as compatibility, a spray test must always be carried out on an inconspicuous area.
- If necessary, apply a second spray coat after 3–6 minutes; several coats are preferable to one thick coat.
- After use, turn the can upside down and spray through the nozzle until only gas comes out, to prevent the valve from sticking.
- Any change in the processing sequence, environmental conditions, non-observance of instructions or the use of products not listed may have an unfavourable effect on the result.

PACHE sarl



ADLER-Werk Lackfabrik, A-6130 Schwaz
Fon: +43/5242/6922-190, Fax: +43/5242/6922-309, Mail: technical-support@adler-lacke.com

Our instructions are based on the current state of knowledge and are intended to advise the buyer/user to the best of our knowledge, but must be individually adapted to the areas of application and processing conditions. The buyer/user is responsible for deciding on the suitability and use of the supplied product, which is why we recommend that a sample be produced to check the suitability of the product. In all other respects, our General Terms and Conditions of Sale apply. All previous data sheets lose their validity with this edition. We reserve the right to make changes to container sizes, color shades and available gloss levels.

**Pache SARL** - 64 Route de Gravin, 74300 Magland
04 50 89 57 17 contact@pache-adler.fr
www.pache-adler.fr



## Application technique

| Application method | Spray can |
|---|---|
| Application quantity ($m^2$ / ml) | 2 - 3 $m^2$ / 150 ml |

## Drying times

(at 23 °C and 50 % rel. humidity)

| | |
|---|---|
| Sandable and recoatable: | approx. 10 - 15 minutes |

The figures given above are reference values. Drying depends on the substrate, layer thickness, temperature, air exchange, relative humidity, stacking pressure and stacking conditions.

Lower temperatures and/or high level of atmospheric humidity can increase the drying time.

## SUBSTRATE

### Type of substrate

Hard and softwood (solid wood-, veneer-, (coated) chipboard-, wood fibre boards)

### Substrate property

The substrate must be dry, clean, capable of holding the paint, free from separating substances such as grease, wax, silicone, resin etc. and free from wood dust, as well as tested for suitability for coating.

### Substrate preparation

**Hardwoods:** Lightly sand with 150 - 180 grit and clean
**Softwoods:** Lightly sand with 100 - 150 grit and clean

## COATING SYSTEM

### Product application

1 – 2 x Grilith Klarlack-Spray (2417)

## ORDERING INFORMATION

### Size of trading unit

150 ml - spray can

### Colour shades / Glosslevels

Grilith Klarlack-Spray Stumpfmatt (2417077812)
Grilith Klarlack-Spray Matt (2417050253)
Grilith Klarlack-Spray Seidenmatt (2417077811)
Grilith Klarlack-Spray Farblos, Glänzend (2417050252)

## FURTHER DETAILS

### Durability / storage



Min. 1 year(s) in the original sealed containers.

Make sure the product is protected against moisture, direct sunlight, frost and high temperatures (above 30 °C).

Close opened containers well and use up the content as soon as possible.

### Safety information

Spray can is under pressure. Store in a well-ventilated place. Keep spray jet away from body. During work, do not eat, drink or smoke. Do not spray against flames or on glowing objects. Even after use do not open it violently or burn it.

Further information on the subject of safety during transport, storage and handling as well as disposal can be found in the relevant safety data sheet. The current version can be accessed on the Internet at **www.adler-lacke.com.**

PACHE SARL