Pache SARL - 64 Route de Gravin, 74300 Magland
04 50 89 57 17 contact@pache-adler.fr
www.pache-adler.fr

Technical data sheet

ADLER
Paint runs through our veins.

Mattkonzentrat 4511

Matting concentrate for **synthetic resin coatings** for DIY, professional and industrial use

PRODUCT DESCRIPTION

Product numbers

4511000210

General

Solvent-based additive for targeted gloss reduction without affecting the fundamental film properties.

Application area

The additive can be used in combination with solvent-based synthetic resin coatings

PROCESSING

Processing instructions

- Please stir and shake the product well before use (1 minute on shaker).
- The temperature of the product and object, and the room temperature must be at least +10 C.
- The gloss level, colour shade, compatibility and adhesion to the substrate must be checked by preparing sample areas.
- Mixed paints must be processed as specified in the corresponding technical data sheet.
- Carefully stir Mattkonzentrat (4511) into the undiluted coating; afterwards stir in the required amount of thinner.
- Any change in the processing sequence, environmental conditions, non-observance of instructions or the use of products not listed may have an unfavourable effect on the result. Deviations lead to film and adhesion problems as well as to impairments with regard to weathering and color stability.

Quantity to be added

For interior products: max. 10%

For exterior products: max. 5%

Drying times
(at 23 °C and 50 % rel. humidity)

The drying behaviour of the coating system is not affected by the addition of Mattkonzentrat (4511).

PACHE sarl

ADLER-Werk Lackfabrik, A-6130 Schwaz
Fon: 0043/5242/6922-190, Fax: 0043/5242/6922-309, Mail: technical-support@adler-lacke.com

Our instructions for use are based on knowledge available currently and shall guide the buyer/user to the best of one's knowledge, but, however, must be clarified for the areas of application and processing conditions on a case-to-case basis. The buyer/user is responsible for deciding on the suitability and use of the delivered product, which is why it is recommended to produce a sample to check the suitability of the product. Our general terms and conditions of sale are otherwise applicable. All previous data sheets are rendered invalid with the issue of this one. Rights reserved for the modification of the container sizes, colour shades and degrees of gloss available.

Pache SARL - 64 Route de Gravin, 74300 Magland
04 50 89 57 17 contact@pache-adler.fr
www.pache-adler.fr

Cleaning the working equipment 8014	With KH-Spritzverdünner (8014) immediately after use. To remove dried product residues we recommend using Clean Abbeizer-Express (8313).

ORDERING INFORMATION

Size of trading unit	1 l

FURTHER DETAILS

Durability / storage 	Min. 5 year(s) in the original sealed containers. Make sure the product is protected against moisture, direct sunlight, frost and high temperatures (above 30 °C). Immediately seal the container to prevent humidity from penetrating.
Safety information 	Further information on the subject of safety during transport, storage and handling as well as disposal can be found in the relevant safety data sheet. The current version can be accessed on the Internet at **www.adler-lacke.com.**

PACHE sarl